

SID

Factory: Rot am See

Article:

ML6

Provided:

Customer:

Date:

03.04.2026

WÜRTH
ELEKTRONIK
MORE THAN
YOU EXPECT

Processtechnology: B: undefined

Material Text	Mat. Nr.	µm	Stackup	Process overview
A-RS Kupferfolie-070my 330x490mm	50200246	70	VS	1
C-RAS-FR4-PP-1080-H63-TG150-HF-EM-37B...	50203000	320		2
A-RAS-FR4-PP-7628-H45-TG150-HF-EM-37B...	50203002	0		3
C-RAS-FR4-PP-1080-H63-TG150-HF-EM-37B...	50203000	0		4
		70	L2	
C-RaS-FR4-DS-0.991mm-070+070-TG150-HF...	50203142	850		5
		70	L3	
C-RAS-FR4-PP-1080-H63-TG150-HF-EM-37B...	50203000	289		6
A-RAS-FR4-PP-7628-H45-TG150-HF-EM-37B...	50203002	0		7
C-RAS-FR4-PP-1080-H63-TG150-HF-EM-37B...	50203000	0		8
		70	L4	
C-RaS-FR4-DS-0.991mm-070+070-TG150-HF...	50203142	850		9
		70	L5	
C-RAS-FR4-PP-1080-H63-TG150-HF-EM-37B...	50203000	320		10
A-RAS-FR4-PP-7628-H45-TG150-HF-EM-37B...	50203002	0		11
C-RAS-FR4-PP-1080-H63-TG150-HF-EM-37B...	50203000	0		12
A-RS Kupferfolie-070my 330x490mm	50200246	70	RS	13

Thickness after Pressing

B00:

3090 µm

Tol+:

320 µm

Tol-:

320 µm

Dmax:

3410 µm

Dmin:

2770 µm

Thickness over all

0 µm

Tol+:

0 µm

Tol-:

0 µm

Dmax:

0 µm

Dmin:

0 µm

Demand for customer

Thickness (D):

3200 µm

Tol+:

320 µm

Tol-:

320 µm

Dmax:

3520 µm

Dmin:

2880 µm

Measuring point: (05) over SM and galv. Cu; both sides

nominal:

3049 µm

Version 1.2.20.35

© Würth Elektronik