

SID

Factory: Rot am See

Article:

ML4

Provided:

Customer:

Date:

31.03.2026

WÜRTH  
ELEKTRONIK  
MORE THAN  
YOU EXPECT

Processtechnology: B: undefined

Material Text	Mat. Nr.	µm	Stackup	Process overview
---------------	----------	----	---------	------------------

A-RS Kupferfolie-035my 330x490mm	50200242	35	VS	1		
A-RAS-FR4-PP-7628-H45-TG150-HF-EM-37B...	50203002	350		2		
C-RAS-FR4-PP-2116-H53-TG150-HF-EM-37B...	50203001	0		3		
C-RAS-FR4-PP-1080-H63-TG150-HF-EM-37B...	50203000	0		4		
		105	L2			
C-RaS-FR4-ML-0.508mm-105+105-TG150-HF...	50203129	510		5	A00	B00
		105	L3			
C-RAS-FR4-PP-1080-H63-TG150-HF-EM-37B...	50203000	350		6		
C-RAS-FR4-PP-2116-H53-TG150-HF-EM-37B...	50203001	0		7		
A-RAS-FR4-PP-7628-H45-TG150-HF-EM-37B...	50203002	0		8		
A-RS Kupferfolie-035my 330x490mm	50200242	35	RS	9		

Thickness after Pressing

B00: 1440 µm Tol+: 155 µm Tol-: 155 µm Dmax: 1595 µm Dmin: 1285 µm

Thickness over all

0 µm Tol+: 0 µm Tol-: 0 µm Dmax: 0 µm Dmin: 0 µm

Demand for customer

Thickness (D): 1550 µm Tol+: 155 µm Tol-: 155 µm Dmax: 1705 µm Dmin: 1395 µm

Measuring point: (05) over SM and galv. Cu; both sides

nominal: 1490 µm

Version 1.2.20.35

© Würth Elektronik