

SID

Factory: Rot am See

Article:

ML6

Provided:

Customer:

Date:

03.04.2026

WÜRTH
ELEKTRONIK
MORE THAN
YOU EXPECT

Processtechnology: B: undefined

Material Text	Mat. Nr.	µm	Stackup	Process overview
A-RS Kupferfolie-070my 330x490mm	50200246	70	VS	1
C-RAS-FR4-PP-1080-H63-TG150-HF-EM-37B...	50203000	245		2
C-RAS-FR4-PP-2116-H53-TG150-HF-EM-37B...	50203001	0		3
C-RAS-FR4-PP-1080-H63-TG150-HF-EM-37B...	50203000	0		4
		70	L2	
C-RS-FR4-ML-0.610mm-070+070-TG150-HF-...	50203086	610		5
		70	L3	
C-RAS-FR4-PP-1080-H63-TG150-HF-EM-37B...	50203000	214		6
C-RAS-FR4-PP-2116-H53-TG150-HF-EM-37B...	50203001	0		7
C-RAS-FR4-PP-1080-H63-TG150-HF-EM-37B...	50203000	0		8
		70	L4	
C-RS-FR4-ML-0.610mm-070+070-TG150-HF-...	50203086	610		9
		70	L5	
C-RAS-FR4-PP-1080-H63-TG150-HF-EM-37B...	50203000	245		10
C-RAS-FR4-PP-2116-H53-TG150-HF-EM-37B...	50203001	0		11
C-RAS-FR4-PP-1080-H63-TG150-HF-EM-37B...	50203000	0		12
A-RS Kupferfolie-070my 330x490mm	50200246	70	RS	13

B00:

Thickness after Pressing

B00:

2290 µm

Tol+:

240 µm

Tol-:

240 µm

Dmax:

2530 µm

Dmin:

2050 µm

Thickness over all

0 µm

Tol+:

0 µm

Tol-:

0 µm

Dmax:

0 µm

Dmin:

0 µm

Demand for customer

Thickness (D):

2400 µm

Tol+:

240 µm

Tol-:

240 µm

Dmax:

2640 µm

Dmin:

2160 µm

Measuring point: (05) over SM and galv. Cu; both sides

nominal:

2344 µm

Version 1.2.20.35

© Würth Elektronik