

SID

Factory: Rot am See

Article:

1026260

ML8

Provided:

Customer:

WE-Direkt

Date:



Processtechnology: B: undefined

Material Text	Mat. Nr.	µm	Stackup	Process overview
A-RS Kupferfolie-018my 330x490mm	50200238	18	VS	1
C-RAS-FR4-PP-1080-H63-TG150-HF-EM-37B...	50203000	62		2
C-RS-FR4-ML-0.107mm-035+035-TG150-HF-...	50203003	35	L2	3 A01
		107		
		35	L3	
C-RAS-FR4-PP-1080-H63-TG150-HF-EM-37B...	50203000	124		4
C-RAS-FR4-PP-1080-H63-TG150-HF-EM-37B...	50203000	0		5
C-RS-FR4-ML-0.107mm-035+035-TG150-HF-...	50203003	35	L4	6 A02
		107		
		35	L5	
C-RAS-FR4-PP-1080-H63-TG150-HF-EM-37B...	50203000	124		7
C-RAS-FR4-PP-1080-H63-TG150-HF-EM-37B...	50203000	0		8
C-RS-FR4-ML-0.107mm-035+035-TG150-HF-...	50203003	35	L6	9 A03
		107		
		35	L7	
C-RAS-FR4-PP-1080-H63-TG150-HF-EM-37B...	50203000	62		10
A-RS Kupferfolie-018my 330x490mm	50200238	18	RS	11

Thickness after Pressing

B00:

890 µm

Tol+:

100 µm

Tol-:

100 µm

Dmax:

990 µm

Dmin:

790 µm

Thickness over all

0 µm

Tol+:

0 µm

Tol-:

0 µm

Dmax:

0 µm

Dmin:

0 µm

Demand for customer

Thickness (D):

1000 µm

Tol+:

100 µm

Tol-:

100 µm

Dmax:

1100 µm

Dmin:

900 µm

Measuring point: (05) over SM and galv. Cu; both sides

nominal:

939 µm

Version 1.2.20.35

© Würth Elektronik