

SID

Factory: Rot am See

Article: 676

ML8

Provided: Stockburger, Olesja

Customer:

Date: 25.01.2016



Processtechnology: B: undefiniert

Material Text	Mat. Nr.	µm	Stackup	Process overview
A-RS Kupferfolie-035my 330x490mm	50200242	35	VS	1
A-RS-FR4-Prepreg-7628-TG150-HF	50200643	210		2
A-RS-FR4-Prepreg-1080-TG150-HF	50200641	0		3
C-RS-FR4-ML-0.25mm-105+105-TG150-HF	50201475	105	L2	4 A01
		250		
		105	L3	
A-RS-FR4-Prepreg-1080-TG150-HF	50200641	230		5
A-RS-FR4-Prepreg-7628-TG150-HF	50200643	0		6
A-RS-FR4-Prepreg-1080-TG150-HF	50200641	0		7
C-RS-FR4-ML-0.25mm-105+105-TG150-HF	50201475	105	L4	8 A02
		250		
		105	L5	
A-RS-FR4-Prepreg-1080-TG150-HF	50200641	230		9
A-RS-FR4-Prepreg-7628-TG150-HF	50200643	0		10
A-RS-FR4-Prepreg-1080-TG150-HF	50200641	0		11
C-RS-FR4-ML-0.25mm-105+105-TG150-HF	50201475	105	L6	12 A03
		250		
		105	L7	
A-RS-FR4-Prepreg-1080-TG150-HF	50200641	210		13
A-RS-FR4-Prepreg-7628-TG150-HF	50200643	0		14
A-RS Kupferfolie-035my 330x490mm	50200242	35	RS	15

Thickness after Pressing

B00: 2290 µm

Tol+: 240 µm

Tol-: 240 µm

Dmax: 2530 µm

Dmin: 2050 µm

Thickness over all

0 µm

Tol+: 0 µm

Tol-: 0 µm

Dmax: 0 µm

Dmin: 0 µm

Demand for customer

Thickness (D): 2400 µm

Tol+: 240 µm

Tol-: 240 µm

Dmax: 2640 µm

Dmin: 2160 µm

Measuring point: (05) über LM und galv.Cu; beidseitig

nominal: 2330 µm

Version 1.2.14.15

© Würth Elektronik